



Loading Position



Draining Position

## Cylinder Upender

### Part Number:

- 25-52-0066: Sngl, 11"
- 25-53-0021: Dual, 11"
- 25-53-0022: Triple, 11"
- 25-52-0023: Sngl, 15"

### Cylinder Size: (Including Valve)

- FMCU-1-11, 11" dia x 60" long
- FMCU-1-15, 15" dia x 60" long

### Dimensions:

- FMCU-1-11  
38" long x 16 1/2" wide x 61 1/2" tall
- FMCU-1-15  
38" long x 20 1/2" wide x 61 1/2" tall

### Warranty:

Two Years

### Model FMCU Manual Upender

#### Features

- Safety Chain
- Welded Steel Frame
- Easy Vertical Loading

# FMCUT-8.5-S Transfill



Load Position

## Cylinder Upender & Transfill



Drain or Transfill Position

A short and compact cylinder upender for draining and/or transfilling short cylinders. Designed for loading cylinders in the vertical position, and equipped with tray handles to easily upend cylinders to the transfill or drain position. Unit size and weight makes it a candidate for a bench top location if needed

### Part Number:

25-51-2197, FMCUT-8.5-S

### Dimensions:

Crated  
Length: 34 in (86 mm)  
Width: 19 in (48 cm)  
Height: 45 in (114 cm)

### Weight:

Unit: 85 lbs (39 kg)  
Crated: 155 lbs (71 kg)

### Warranty:

Two Years!

### Model FMCUT -8.5-S

#### Features

- Safety Chain
- Welded Steel Frame
- Easy Vertical Loading
- Upending Handles
- Max Cyl. Size with Valve:  
8 1/2 Dia x 34" L

Contact factory for any  
special size requirements

# Model FMCUT Series



Load Position



Transfill Position

## Cylinder Upender & Transfill

### Part Number:

25-51-0273, FMCUT-1-11  
25-51-0274, FMCUT-1-15

### Dimensions:

FMCUT-1-11  
Length: 38 in (97 mm)  
Width: 16.5 in (42 cm)  
Height: 64 in (163 cm)

FMCUT-1-15  
Length: 38 in (97 mm)  
Width: 20.5 in (52 cm)  
Height: 64 in (163 cm)

### Weight:

FMCUT-1-11, 142 lbs (64.5 kg)

### Max Cylinder Size: (Including Valve)

FMCUT-1-11, 11" dia x 64" long  
FMCUT-1-15, 15" dia x 64" long

### Warranty:

Two Years

### Model FMCUT Series

#### Features

- Safety Chain
- Welded Steel Frame
- Easy Vertical Loading

# FHDCU Series Upender



## Cylinder Upender, Heavy-Duty Hydraulic Control

### Part Number:

25-51-2110, 1 Station Upender  
25-51-1011, 2 Station Upender

### Cylinder Range:

Cylinder Diameter to 24 in (61 cm)  
Cylinder Length to 120 in (305 cm)

### Warranty:

Two Years

### Model FHDCU-2-24 Series Cylinder Upender

### Features

- Hydraulic Control
- Dual Grip, Four Position Arms
- Heavy-duty Welded Steel Frame
- Safety Urethane "No Mark" Safety Grips

**Fredløv™** Incorporated

# FHDCU Series Upender



## 3 Station Cylinder Upender, Heavy-Duty Hydraulic Control

### Model FHDCU-3-24 Series Cylinder Upender

#### Cylinder Range:

Cylinder Diameter 24" (55.9 cm)  
Cylinder Length to 10ft

#### Warranty:

Two Years

#### Features

- Hydraulic Control
- Dual Grip, Four Position Arms
- Heavy-duty Welded Steel Frame
- Safety Urethane "No Mark" Safety Grips

**Fredløv™** Incorporated



FCU-2-12-M



FACU-1-16-M  
(with optional casters)



FACU-1-16-M



Simple Control Panel

## Cylinder Upender (Manual/Pneumatic)

This manual-pneumatic unit allows the operator to clamp and upend the cylinder with 2 simple controls (clamp and invert) and cyl can stop at any upend position by releasing the upend control valve. Used for inspection of foot rings / plugs, or draining cylinder, units are also available with drying capabilities as an option. Since unit is built using no electrical components, it eliminates the need for "Explosion Proofing".

### Part Numbers:

25-53-0015, FCU-1-16-M  
 25-52-0425, FCU-1-16-M-WC (casters)  
 25-51-2170, FCU-1-16-M-D (w/drying)  
 25-51-2170, FCU-2-12-M  
 25-52-0270, FCU-2-16-M  
 25-52-0462, FCU-3-16-M  
 25-52-0271, FCU-4-16-M  
 25-51-2000, FCU-6-10-M

25-52-0415 FACU-1-16-M  
 25-52-0425 FACU-1-16-M -WC (casters)

### Air Requirements:

120 psig min filtered & lubricated

### Warranty:

Two Years

### Cylinder Upender (Manual/Pneumatic)

#### Features

- Safety orange "No Mark" cyl. grips
- Standard or grip arms lowered (FACU) for Acetylene type cylinders
- Max.cyl weight: 500 lbs (227 kg)
- Cylinder diameter range based on models type (4" to 16" dia.)
- Optional casters available for all models
- Optional drying capabilities available)
- Equipped with a short cyl stand on FCU units

Fredløv™ Incorporated

Para más información comuníquese al  
305.888.5353  
o al correo electrónico  
[info@intltec.com](mailto:info@intltec.com)

